

RECEIVED  
GENERAL FAX CENTER  
OCT 03 2006

Application No. 10/721,681  
Amendment dated October 3, 2006  
Reply to Office Action of April 4, 2006

**Amendments to the Claims:**

This listing of claims will replace all prior versions, and listings, of claims in the application:

**Listing of Claims:**

Claims 1-38. (Cancelled)

39. (original) A surgical ligation clip for ligating a fluid carrying structure, said clip comprising:

a mid-longitudinal axis, a distal end, a proximal end opposite said distal end, and a length between said distal and proximal ends;

an upper support member extending between said distal and proximal ends;

a lower support member extending between said distal and proximal ends, said lower support member being opposite said upper support member in a vertical plane parallel to the mid-longitudinal axis; and

a connector at said proximal end of said clip, said connector joining said upper and lower support members, each of said upper and lower support members including an enlarged section proximate said distal end, each of said enlarged sections having a clamping surface adapted to clamp the fluid carrying structure therebetween, said enlarged section including a central axis generally transverse to said clamping surface, said enlarged section having an exterior surface forming an arc extending more than 180 degrees around the central axis in a plane generally transverse to the central axis.

40. (original) The clip of claim 39, wherein said exterior surface includes two opposed portions that form an arc of a circle in a plane generally transverse to the central axis.

41. (original) The clip of claim 39, wherein said clip is formed of a single piece of wire and has a first free end terminating at said connector and a second free end

Application No. 10/721,681  
Amendment dated October 3, 2006  
Reply to Office Action of April 4, 2006

terminating at one of said enlarged sections.

42. (original) The clip of claim 39, wherein each of said enlarged sections have a clamping surface adapted to clamp the fluid carrying structure therebetween, said clamping surfaces having a maximum separation distance therebetween of 0.75 mm in an open and undeployed position.
43. (original) The clip of claim 39, wherein said connector is adapted to bias said upper and lower support members toward one another into a closed position.
44. (original) The clip of claim 39, wherein said connector includes a coil spring.
45. (original) The clip of claim 39, wherein said connector is adapted to apply a force to said upper and lower support members to bias said upper and lower support members toward one another into a closed position, the force being greater than that needed to move said upper and lower support members into contact with one another.
46. (original) The clip of claim 39, wherein said connector includes a pre-load force between said upper and lower support members of at least 100 grams of force.
47. (original) The clip of claim 39, wherein said clip has a maximum dimension of 5 mm transverse to the mid-longitudinal axis.
48. (original) The clip of claim 39, in combination with a clip applier for applying said clip to the fluid carrying structure.
49. (original) The clip of claim 48, wherein said clip applier includes a magazine adapted to hold a plurality of clips.
50. (original) The clip of claim 39, wherein the fluid carrying structure is a vessel, at least one of said upper and lower support members having a surface configured to enhance gripping of the vessel.